

Unshielded Radial Power Inductor

AIUR-06 Series



RoHS
Compliant



18.03 x ϕ 12.7mm

FEATURES:

- Ferrite core with heat shrink tube
- High Reliability

APPLICATIONS:

- Switching Power Supplies
- Noise Filtering
- DC to DC Converters
- Electronic Household Appliances
- Buzzers and Alarm Systems
- Television and Audio Equipment

STANDARD SPECIFICATIONS:

PARAMETERS

ABRACON P/N:	AIUR-06 Series
Operating temperature:	-55°C to + 85°C with full rated current, -55°C ~ +125°C with no load.
Storage temperature:	-40°C to + 85°C

Part Number	Inductance	Tolerance	DCR (Max)	Saturation Current (Max)	Inductance Code
Units	μ H	%	Ω	A	
Symbol	L	K	DCR	IDC	
AIUR-06-3R9	3.9	K	0.016	14.2	3R9K
AIUR-06-4R7	4.7	K	0.018	13.0	4R7K
AIUR-06-5R6	5.6	K	0.021	11.0	5R6K
AIUR-06-6R8	6.8	K	0.023	10.0	6R8K
AIUR-06-8R2	8.2	K	0.026	9.5	8R2K
AIUR-06-100	10	K	0.031	8.8	100K
AIUR-06-120	12	K	0.036	7.9	120K
AIUR-06-150	15	K	0.040	7.1	150K
AIUR-06-180	18	K	0.041	7.4	180K
AIUR-06-220	22	K	0.043	6.1	220K
AIUR-06-270	27	K	0.046	5.5	270K
AIUR-06-330	33	K	0.051	5.2	330K
AIUR-06-390	39	K	0.054	4.5	390K
AIUR-06-470	47	K	0.063	4.1	470K
AIUR-06-560	56	K	0.075	3.8	560K
AIUR-06-680	68	K	0.078	3.5	680K
AIUR-06-820	82	K	0.088	3.1	820K
AIUR-06-101	100	K	0.108	2.8	101K
AIUR-06-121	120	K	0.127	2.6	121K
AIUR-06-151	150	K	0.162	2.4	151K
AIUR-06-181	180	K	0.228	2.1	181K
AIUR-06-221	220	K	0.252	1.9	221K
AIUR-06-271	270	K	0.270	1.75	271K
AIUR-06-331	330	K	0.394	1.62	331K
AIUR-06-391	390	K	0.416	1.40	391K
AIUR-06-471	470	K	0.568	1.30	471K
AIUR-06-561	560	K	0.650	1.20	561K
AIUR-06-681	680	K	0.740	1.10	681K
AIUR-06-821	820	K	1.0	0.96	821K
AIUR-06-102	1000	K	1.2	0.88	102K
AIUR-06-122	1200	K	1.5	0.80	122K
AIUR-06-152	1500	K	1.7	0.72	152K
AIUR-06-182	1800	K	1.8	0.66	182K
AIUR-06-222	2200	K	2.4	0.60	222K
AIUR-06-272	2700	K	2.8	0.54	272K
AIUR-06-332	3300	K	3.7	0.48	332K
AIUR-06-392	3900	K	5.0	0.42	392K
AIUR-06-472	4700	K	5.6	0.40	472K
AIUR-06-562	5600	K	6.3	0.37	562K
AIUR-06-682	6800	K	8.4	0.34	682K
AIUR-06-822	8200	K	9.6	0.31	822K
AIUR-06-103	10000	K	10.5	0.29	103K
AIUR-06-123	12000	K	14.5	0.25	123K
AIUR-06-153	15000	K	20.5	0.23	153K

Test Conditions and equipments

Test frequency: 1kHz, 0.1Vrms

IDC: max. 10% inductance drop from initial value

ABRACON IS
ISO 9001:2008
CERTIFIED



ABRACON
CORPORATION

Visit www.abracon.com for Terms & Conditions of Sale

Revised: 08.08.12

30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Unshielded Radial Power Inductor

AIUR-06 Series

 **RoHS**



18.03 x ϕ 12.7mm

PART IDENTIFICATIONS:

AIUR-06-


Inductance Code

Please refer to the Electrical Spec Table

Tolerance

K: $\pm 10\%$

OUTLINE DRAWING:



Dimension: mm

Packing (250pcs / Box)

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO 9001:2008
CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale

Revised: 08.08.12

30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com