

## Specification Sheet

Part Number: 596-00185



Thermal Transfer Labels, 1.85" x .5", For Use On White Insert 596-00419, PET, White 500/roll

|                                |   |
|--------------------------------|---|
| <b>Article Number</b>          | 596-00185   |
| <b>Type</b>                    | NPL47X13  |
| <b>Color</b>                   | White (WH)  |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.</li><li>• Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.</li><li>• Labels are UV and chemical resistant for long life in an industrial environment.</li><li>• Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.</li></ul> |
| <b>Quantity Per</b>            | roll  |

**Product Description**

Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Short Description**

Thermal Transfer Labels, 1.85" x .5", For Use On White Insert 596-00419, PET, White 500/roll

**Global Part Name**

NPL47X13-PET-WH

**Technical Description**

Thermal Transfer Label, 1.85" X .5", For Use On White Insert 596-00419, PET

**Width W (Imperial)**

1.85

**Width W (Metric)**

46.9

**Height H (Imperial)**

.50

**Height H (Metric)**

12.70

**Width of Liner (Metric)**

50.16

**Width of Liner (imperial)**

1.975

**Material**

Polyester (PET)

**Material Shortcut**

PET

**Adhesive**

Acrylate with base of acrylic foam

**Halogen free** No

**Adhesive Operating Temperature** -40°F to +176°F (-40°C to +80°C)

**Operating Temperature (Metric)** -40°F to +302°F (-40°C to +150°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3919102055

**Content Unit(BMEcat)** pcs.

**Labels per Column** 1

**Labels per Row** 1

**Weight (Metric)** 0.22

**Weight (Imperial)** 0.5